

**mase**  
**GENERATORS**



# LT 10060 L

**mase**  
**GENERATORS**  
**NORTH AMERICA**

3125 John P Curcie drive Bay #6  
Pembroke Park, Florida 33009  
Ph. +1 754-703-5153  
Fax +1 754-703-5154  
[www.MaseNorthAmerica.com](http://www.MaseNorthAmerica.com)  
[info@masenorthamerica.com](mailto:info@masenorthamerica.com)

**SUPER SILENCED SINGLE-PHASE POWER GENERATOR /  
 OUTPUT POWER 10 kW SINGLE-PHASE / DIESEL ENGINE 1800 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"> <li>+ Control panel with voltmeter and hour meter; with auto engine protection shutdown system in case of:</li> <li>+ low oil pressure</li> <li>+ high engine temperature</li> <li>+ 12V built-in battery with electric start</li> <li>+ fuel level gauge</li> <li>+ emergency stop push-button</li> <li>+ 120-240V single-phase socket protected by circuit breaker</li> <li>+ 3 stabilizers</li> <li>+ 8 mt lighting tower with 4x1500W halogen lamps</li> <li>+ 2 wheels site tow undercarriage</li> </ul>	
<b>Options</b> (available as factory options)	<ul style="list-style-type: none"> <li>+ floodlight with metal halide lamps</li> <li>+ floodlight with LED lamps</li> <li>+ hydraulic lifting</li> <li>+ 2 wheels road tow</li> <li>+ low temperature kit</li> <li>+ dusk sesor</li> <li>+ homologation to directive 2000/14/EC</li> </ul>	
<b>Accessories on Request</b>	<ul style="list-style-type: none"> <li>+ not available</li> </ul>	
<b>Noise Level</b>	<ul style="list-style-type: none"> <li>+ Lwa 97 (72 dB a 7 m)</li> </ul>	
<b>AC Generator 60 Hz</b>	<ul style="list-style-type: none"> <li>+ type: synchronous</li> <li>+ single-phase power (stand by): 10 kW - 230 V</li> <li>+ single-phase power (prime): 9 kW - 230 V</li> <li>+ power Factor: <math>\cos\Phi</math> 0.8</li> </ul>	
<b>Diesel Engine 1800 rpm</b>	<ul style="list-style-type: none"> <li>+ type: Lombardini LDW 1003 - 3 cyl. 13.4 HP - 1028 cm<sup>3</sup></li> <li>+ fuel: diesel</li> <li>+ cooling system: water</li> <li>+ starting system: electric</li> <li>+ fuel tank capacity: 100 L</li> <li>+ fuel consumption @ 75%: 2,4 L/h</li> </ul>	
<b>Other Features</b>	<ul style="list-style-type: none"> <li>+ insulation Class: H</li> <li>+ ambient temperature: 40 °C (*)</li> <li>+ altitude: 1000 mt (*)</li> <li>+ mechanical Protection: IP 23</li> <li>+ dimensions (L x W x H): 2935 x 1522 x 2395 mm</li> <li>+ dimensions of the machine in operation (L x W x H): 2935 x 2612 x 8000 mm</li> <li>+ dry weight: 655 kg</li> </ul>	

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.