

mase
GENERATORS



LT 10060 P

mase
GENERATORS
NORTH AMERICA

3125 John P Curcie drive Bay #6
Pembroke Park, Florida 33009
Ph. +1 754-703-5153
Fax +1 754-703-5154
www.MaseNorthAmerica.com
info@masenorthamerica.com

**SUPER SILENCED SINGLE-PHASE POWER GENERATOR /
 OUTPUT POWER 10 kW SINGLE-PHASE / DIESEL ENGINE 1800 RPM**

Gen Set Features	<ul style="list-style-type: none"> + Control panel with voltmeter and hour meter; with auto engine protection shutdown system in case of: + low oil pressure + high engine temperature + 12V built-in battery with electric start + fuel level gauge + emergency stop push-button + 120-240V single-phase socket protected by circuit breaker + 3 stabilizers + 8 mt lighting tower with 4x1500W halogen lamps + 2 wheels site tow undercarriage
Options (available as factory options)	<ul style="list-style-type: none"> + floodlight with metal halide lamps + floodlight with LED lamps + hydraulic lifting + 2 wheels road tow + low temperature kit + dusk sesor + homologation to directive 2000/14/EC
Accessories on Request	<ul style="list-style-type: none"> + not available
Noise Level	<ul style="list-style-type: none"> + Lwa 97 (72 dB a 7 m)
AC Generator 60 Hz	<ul style="list-style-type: none"> + type: synchronous + single-phase power (stand by): 10 kW - 230 V + single-phase power (prime): 9 kW - 230 V + power Factor: $\cos\Phi$ 0.8
Diesel Engine 1800 rpm	<ul style="list-style-type: none"> + type: PERKINS 403D-11G - 3 cyl. 15.3 HP - 1028 cm³ + fuel: diesel + cooling system: water + starting system: electric + fuel tank capacity: 100 L + fuel consumption @ 75%: 2,4 L/h
Other Features	<ul style="list-style-type: none"> + insulation Class: H + ambient temperature: 40 °C (*) + altitude: 1000 mt (*) + mechanical Protection: IP 23 + dimensions (L x W x H): 2935 x 1522 x 2395 mm + dimensions of the machine in operation (L x W x H): 2935 x 2612 x 8000 mm + dry weight: 655 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.