

mase

GENERATORS



LT 6060 Y

CE

mase
GENERATORS
NORTH AMERICA

2060 NW 29 Th St. Oakland Park
Florida 33311
Ph. + 1 954-990-4130 or 954-533-2701
www.masenorthamerica.com
info@masenorthamerica.com

LT 6060 Y

LIGHTING TOWER - SINGLE-PHASE POWER GENERATOR / SILENCED VERSION / DIESEL ENGINE 3600 RPM

Standard Features	<ul style="list-style-type: none"> + Control panel with: <ul style="list-style-type: none"> - hour meter - earth leakage circuit breaker - lamps switch - 115 V single-phase socket protected by circuit breaker - warning lights for: <ul style="list-style-type: none"> low oil pressure battery charger failure voltage ON - auto engine protection shutdown system in case of: <ul style="list-style-type: none"> low oil pressure battery charger failure 	<ul style="list-style-type: none"> + 12 V built-in battery + Fuel level gauge + Emergency stop button + 7 mt lighting tower (340° rotation) with - 4 x 1000 W halogen lamps - manual lifting system + 3 stabilizers + Two-wheels site tow undercarriage (GRT2W)
Options (available as factory options)	<ul style="list-style-type: none"> + 4 x 400 W HPS lamps (high pressure sodium) + 4 x 1000 W HPS lamps (high pressure sodium) 	
Noise level	+ Lwa 95 (70 dB at 7 m)	
AC Generator 60 Hz	<ul style="list-style-type: none"> + Type: synchronous + Single-phase power (stand by): 7,5 kVA - 115 V + Power factor: $\cos \varphi 0,8$ 	
Lighting tower	<ul style="list-style-type: none"> + Lamp: halogen + Power A.C.: 4 x 1000W + Lumen: 80.000 + Illuminated area: 1600 mq + Lifting: with manual winch + Brake: automatic 	<ul style="list-style-type: none"> + Lamp: HPS + Power A.C.: 4 x 400W + Lumen: 200.000 + Illuminated area: 3000 mq + Lifting: with manual winch + Brake: automatic
EPA Diesel Engine 3600 rpm	<ul style="list-style-type: none"> + Type: Yanmar L100N - 1 cyl. 10 HP (7,4 kWm) - 435 cm³ + Fuel: diesel + Cooling system: air + Starting system: electric + Fuel tank capacity: 100 l + Fuel consumption @ 75%: 1,7 l/h 	
Other Features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 mt (*) + Mechanical Protection: IP 23 + Dimensions (Lu x La x H): 2548 x 1520 x 2488 mm + Dimensions of the machine in operation (Lu x La x H): 2548 x 2604 x 8000 mm + Dry weight: 520 kg 	

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.