

GenSet



MG 10000 S-KL



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy
Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244
E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

MG 10000 S-KL

SINGLE-PHASE POWER GENERATOR / OUTPUT POWER 10 KVA SINGLE-PHASE / DIESEL ENGINE 1800 RPM

Gen Set Features

- + DAS, auto engine protection shutdown system, with warning lights in case of:
 - battery charger failure
 - high coolant temperature
 - low fuel level
 - low oil pressure
- + 12 V built-in battery with electric start
- + Voltmeter
- + Engine hourmeter
- + Emergency stop button
- + Earth Leakage Circuit Breaker (ELCB)
- + 1x32 A, 240 V - 60 Hz single-phase EEC socket protected by circuit breaker
- + 240 V - 60 Hz single-phase output protected by circuit breaker
- + 1x32 A, 120 V - 60 Hz single-phase EEC socket protected by circuit breaker
- + 120 V - 60 Hz single-phase output protected by circuit breaker
- + Fork lift pockets

Gen Set Options (available as factory options)

- + Versions with different voltages
- + 50 Hz version

Accessories on Request

- + Trolley: two-wheels and handles

Noise Level

- + Lwa 96

AC Generator 50 Hz

- + Type: synchronous
- + Single-phase power (stand by): 10 kVA - 240 V
- + Single-phase power (prime): 9 kVA - 240 V
- + Single-phase power (prime): 4 kVA - 120 V
- + Power Factor: $\cos \varphi 0,8$

Diesel Engine 1500 rpm

- + Type: Kubota D1105-E - 3 cyl. 15,4 HP (11,5 kWm) - 1123 cm³
- + Fuel: diesel
- + Cooling system: water
- + Starting system: electric
- + Fuel tank capacity: 40 l
- + Fuel consumption @ 75%: 247 g/kWh

Other Features

- + Insulation Class: H
- + Ambient temperature: 40 °C (*)
- + Altitude: 1000 mt (*)
- + Mechanical Protection: IP 23
- + Dimensions (L x W x H): 1357 x 707 x 942 mm
- + Dry weight: 350 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.